

## **SPECIFICATIONS**

**ENGINE** Type

Air cooled, 4 - stroke single cylinder OHC

124.7 c.c Displacement

Maximum Power 6.72 kW (9 bhp)@7000 rpm Maximum Torque 10.35 N-m @ 4000 rpm

Bore x Stroke 52.4 x 57.8 mm

Compression Ratio 9.1:1

Self Start / Kick Start Starting

Ignition AMI - Advanced Microprocessor Ignition System

**TRANSMISSION** 

Multiplate wet Clutch

Gear box 4 Speed constant mesh

CHASSIS Type

Tubular Double Cradle Type

SUSPENSION

Front Telescopic Hydraulic Shock Absorbers Swing Arm with Hydraulic Shock Absorbers Rear

**BRAKES** 

Front Disc 240 mm Dia; Pad - Non Asbestos type Drum

Internal expanding shoe type - 130 mm

Liners - Non Asbestos type

Rear Drum Internal expanding shoe type - 130 mm

Liners - Non Asbestos type

WHEELS AND TYRES

Front 18 x 1.60, Spoke Wheel /Cast Wheel Rim Size

Rear 18 x 1.60, Spoke Wheel / Cast Wheel

Tyre Size Front 2.75 x 18 - 42 P / 4 PR Rear 3.00 x 18 - 52 P / 6 PR

**ELECTRICALS** 

Battery 12 V - 3 Ah MF Battery

Head Lamp 12 V - 35 W / 35 W - Halogen Bulb

(Multi-Reflector Type)

Tail / Stop Lamp 12 V - 5 / 21 W (Multi-Reflector)

Turn Signal Lamp 12 V - 10 W (Amber Bulb) x 4 nos

(MFR - Clear Lens)

Engine oil grade SAE 10 W 30 SJ Grade Fuel tank capacity 13.6 litre (Min)

Reserve

1 litre (usable reserve)

**DIMENSIONS** 

LxWxH 2005 X 735 X 1070 mm

Wheelbase 1265 mm Ground clearance 150 mm

**WEIGHTS** 

Kerb weight 125 Kg (Kick) / 129 Kg(Self)









Warranty for a period of 5 years or 70,000 kms from the date of purchase whichever is earlier.

Accessories shown may not be a part of standard equipment. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Glamour meets latest emission norms.



Hero MotoCorp Ltd., 34, Basant Lok, Vasant Vihar, New Delhi -110 057, Phone: 011- 4604 4100 Fax:011-2614 3312, 2614 3198. www.heromotocorp.com