

Leaflet, Size: 10.5 x 8.5 inches, Bleed 5 mm extra (Job No.: HMC1100156) dt. 11/04/13

Solid like you

Features

ENGINE

SUSPENSION

Front



Solid Comfort

Specially designed seat

for that great

riding experience



Best mileage in 150cc category



Solid Power


150cc ATFT engine
for perfect balance of
power and fuel economy



5 Spoke black alloy wheels

18 X 1.60, Cast Wheel

18 X 1.60, Cast Wheel



Tube with puncture endurance for enhanced safety

AVAILABLE IN 5 EXCITING COLOURS



Rim Size Front

Rim Size Rear









Magnetic Blue

Туре	Air cooled, 4 – Stroke single cylinder OHC
Bore X Stroke	57.3 X 57.8 mm
Displacement	149.1cc
Compression Ratio	9.1 : 1
Maximum Power	10 kW (13.6 Ps) @ 8000 rpm
Maximum Torque	12.80 N m @ 5000 rpm

Technical Specifications

Ignition Advanced Micro Processor Ignition System (AMI)
Starting Kick Start / Self Start

TRANSMISSION

Clutch Multiplate Wet
Gear Box 5 Speed Constant Mesh, Heel & Toe Shift

CHASSIS

Type Tubular Diamond Type

Telescopic Hydraulic Shock Absorbers

Rectangular Swing Arm with Adjustable Hydraulic Shock Absorbe

It is our endeavor to constantly improve our products. This could lead to changes in product specifications without prior notice. Achiever complies with the latest emission norms.



	Tyre Size Front Tyre Size Rear Brakes Front Brakes Rear	2.75 X 18 – 42 P/ 4 PR 3.00 X 18 – 52 P/ 6 PR (Tube with Puncture Endurance) Disc (240 mm) Internal Expanding Shoe Type (130 mm)
	ELECTRICALS	
	Battery Head Lamps Tail / Stop Lamp	12 V - 2.5 Ah (Kick) / 7 Ah (Self) 12 V - 35 W / 35 W - Halogen Bulb (Multi-Reflector Type) 12 V - 5 W / 21 W (Multi-Reflector Type)
	DIMENSIONS	
	Length Width Height Wheelbase Ground Clearance	2040 mm 760 mm 1120 mm 1290 mm 160 mm
oro	WEIGHTS	
ers	Korh Woight	124 kg (Viola) / 120 kg (Colf)

Kerb Weight Max Payload 130 kg
Fuel Tank Capacity Reserve 130 kg (Kick) / 138 kg (Self) 130 kg 12.5 litre (Usable Reserve)



Authorised Dealer

