

ab sirf **style** hi
style bolega

 **Hero**



Attractive Visor



Digital-analog combo meter console



Designer Graphics



Radical Twin Bulb Tail Light



Passion
PRO



S P E C I F I C A T I O N S

ENGINE

Type	Air cooled , 4 - stroke single cylinder OHC
Displacement	97.2 cc
Maximum Power	5.74 kW (7.8 Ps) @ 7500 rpm
Maximum Torque	8.04 N-m @ 4500 rpm
Bore x Stroke	50.0 x 49.5 mm
Carburettor	Side Draft, Variable venturi Type with TCIS
Ignition	DC - Digital CDI

TRANSMISSION

Gear Box	4 Speed constant mesh
----------	-----------------------

CHASSIS

Type	Tubular, Double Cradle frame
------	------------------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with adjustable Hydraulic Shock Absorbers

BRAKES

Front	Drum	Internal expanding shoe type - 130 mm
	Disc	240 mm Dia Disc
Rear	Drum	Internal expanding shoe type - 130 mm

WHEEL AND TYRES

Rim Size	Front	18 x 1.60, Spoke Wheel / Cast Wheel
	Rear	18 x 1.60, Spoke Wheel / Cast Wheel
Tyre Size	Front	2.75 x 18 - 42 P/ 4 PR
	Rear	3.00 x 18 - 52 P/ 6 PR

ELECTRICALS

Battery	12 V - 3 Ah, MF Battery
Head Lamp	12 V - 35 W / 35 W - Halogen Bulb, Trapezoidal, MFR
Tail/Stop Lamp	12 V - 5 W / 10 W (Twin Bulb), Multi Reflector
Turn Signal Lamp	12 V - 10 W (Amber Bulb) x 4 Nos. MFR, Clear Lens

DIMENSIONS

Length x Width x Height	1980 x 725 x 1075 mm
Wheelbase	1235 mm
Saddle Height	795 mm
Ground Clearance	165 mm

WEIGHTS

Fuel Tank Capacity	12.8 Litre (Min), 1 Litre (Usable Reserve)
Kerb Weight	116 Kg (Kick), 119 Kg (Self)



SPORTS RED



BLACK WITH SPORTS RED



VIBRANT BLUE



BLACK WITH HEAVY GREY



BLACK WITH FROST BLUE



LEAF GREEN METALLIC



FORCE SILVER



Hero MotoCorp Ltd.

34, Basant Lok, Vasant Vihar, New Delhi-110 057, Phone: 011-46044100
Fax: 011-26143321 / 26143198 www.heromotocorp.com

*Warranty for a period of 5 years or 70000 kms from the date of purchase, whichever is earlier. Hero Passion Pro complies with BS III emission norms. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Accessories shown may not be part of standard fitment.