



***SIMPLY SUPER***

*super*  
*All New Splendor*





# All New Super Splendor

"Its not always that you will come across something that redefines your experience of riding a bike. Its rare to get a perfect combination of unbeatable mileage and power. Its only when you have the strength of all black alloys and a dash of chrome that commands attention combined with the trust of ever reliable ASFS engine."



*Exciting New Graphics*



*Stylish New Alloy Wheels*



*Classy Tail Light*



*Attractive Meter Console*

**ASFS**  
Advanced swirl flow induction system

The new age ASFS engine delivers better mileage and performance. It creates a perfect swirling motion of air and fuel mixture inside the combustion chamber for faster and improved burning. It extracts the best out of each drop of fuel, resulting in better fuel economy and lower emissions. If you want to make every drop of fuel count and do your bit to conserve the environment, go ahead and ride the ASFS technology.



Cloud Silver



Candy Blazing Red



Heavy Grey



Graphite Black



Vibrant Blue



Black With Fiery Red



Black with Electric Purple



Hero MotoCorp Ltd.,  
34, Basant Lok, Vasant Vihar,  
New Delhi -110 057, Phone: 011- 4604 4100  
Fax:011- 2614 3312, 2614 3198.  
[www.heromotocorp.com](http://www.heromotocorp.com)



Warranty for a period of 5 years  
or 70,000 kms from the date of purchase,  
whichever is earlier.

Accessories shown may not be a part of standard fitment. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Super Splendor complies with latest emission norms.

## TECHNICAL SPECIFICATION

<b>ENGINE</b>		
Type		Air cooled, 4 - Stroke Single Cylinder OHC
Bore x Stroke		52.4 x 57.8 mm
Displacement		124.7 cc
Compression Ratio		9.1 : 1
Maximum Power		6.72 kW ( 9.12 Ps ) @ 7000 rpm
Maximum Torque		10.35 N m @ 4000 rpm
Ignition		Advanced Micro Processor Ignition System ( AMI )
Starting		Kick Start / Self Start
<b>TRANSMISSION</b>		
Clutch		Multi Plate Wet
Gear Box		4 Speed Constant Mesh
<b>CHASSIS</b>		
Type		Tubular Double Cradle Type
<b>SUSPENSION</b>		
	Front	Telescopic Hydraulic Shock Absorbers
	Rear	Swing Arm with 5 step adjustable Hydraulic Shock Absorbers
<b>WHEELS AND TYRES</b>		
Rim Size	Front	18 x 1.60, Cast Wheel
	Rear	18 x 1.60, Cast Wheel
Tyre Size	Front	2.75 x 18 - 42 P / 4 PR
	Rear	2.75 x 18 - 48 P / 6 PR
Brakes	Front	Internal Expanding Type ( 130 mm )
	Rear	Internal Expanding Type ( 130 mm )
<b>ELECTRICALS</b>		
Battery		MF Battery, MF - 4 : 12 V 4 Ah
Head Lamp		12 V - 35 W / 35 W - Halogen Bulb ( Multi - Reflector Type )
Tail / Stop Lamp		5 W / 21 W ( Multi - Reflector Type )
<b>DIMENSIONS</b>		
Length		1995 mm
Width		735 mm
Height		1095 mm
Wheel Base		1265 mm
Ground Clearance		150 mm
<b>WEIGHTS</b>		
Kerb Weight		121 kg ( Self )
Max Payload		130 kg
Fuel Tank Capacity		13 Litre ( Min )
Reserve		1 Litre ( Usable Reserve )

**AUTHORISED DEALER:**